



Status:	Ok
Approval:	10.11.2023

<b>Classification</b>	Public series
Product type:	Foam abrasives
Main industries:	Building Interior
Further industries:	Kitchens Windows and Doors Marine


<b>Product profile</b>	
Grit type:	Aluminium oxide
Grit range (total):	180; 240; 320
Backing:	Mesh
Coating:	Mechanical
Bonding:	Elastic binder
Special coating:	
Equipment:	




<b>Properties</b>		<b>Technology</b>
Removal rate:	8 - high	
Lifetime:	9 - very long	
Finishing:	8 - good	
Flexibility:	10 - highly flexible	
Contact pressure:	7 - strong	

<b>Advantages</b>	
Building Interior:	<ul style="list-style-type: none"> <li>- Maximum useful life</li> <li>- Highly adaptable to contours, curves and profiles</li> <li>- Low clogging</li> <li>- Can be used many times</li> <li>- Consistent performance throughout the life of the product</li> <li>- Can be used wet or dry</li> </ul>

<b>Applications</b>	
Building Interior:	<ul style="list-style-type: none"> <li>- Sanding off old varnish, paints and stains</li> <li>- Sanding off raised wooden fibres</li> <li>- Keying surfaces for better paint adhesion</li> </ul>

<b>Material</b>		
Building Interior:	<ul style="list-style-type: none"> <li>Bodyfiller</li> <li>Lacquers</li> <li>Lacquers</li> <li>Lacquers</li> <li>Lacquers</li> <li>Lacquers</li> <li>Metals</li> <li>Mineral materials</li> <li>Old lacquer</li> <li>Old paint</li> <li>Paints</li> <li>Plaster</li> <li>Primer filler</li> <li>Wood</li> <li>Wood</li> </ul>	<ul style="list-style-type: none"> <li><input type="radio"/> Acrylic glass</li> <li><input type="radio"/> Plastics</li> <li><input type="radio"/> Melamine sheet</li> <li><input type="radio"/> Bodyfiller</li> <li><input checked="" type="radio"/> Water-based lacquer</li> <li><input checked="" type="radio"/> UV lacquer</li> <li><input checked="" type="radio"/> Polyester lacquer</li> <li><input type="radio"/> NC lacquer</li> <li><input checked="" type="radio"/> PU lacquer</li> <li><input checked="" type="radio"/> Stainless steel (inox)</li> <li><input type="radio"/> Solid surface material</li> <li><input checked="" type="radio"/> Old lacquer</li> <li><input checked="" type="radio"/> Old paint</li> <li><input checked="" type="radio"/> Colour</li> <li><input type="radio"/> Plaster</li> <li><input checked="" type="radio"/> Primer filler</li> <li><input checked="" type="radio"/> Hard wood</li> <li><input checked="" type="radio"/> Soft wood</li> </ul>

<b>Conversion forms</b>	Upper conversion	Lower conversion
	Sheet	- Half sheets

<b>Application</b>	Superordinate group	Subgroup
	Manual sanding	Manual sanding
	Manual sanding	Hand sanding for profiles
	Manual sanding	Hand sanding for edges
Cut:	Dry application, Wet sanding	

<b>Details</b>	
No suitability for:	
Sanding recommendation:	
Safety recommendation:	Observe the current valid safety recommendations at: <a href="http://www.sia-abrasives.com">www.sia-abrasives.com</a> > Expertise > Safety

