## **Technical data sheet** 8933 siagrind



Status:	Ok
Approval:	06.08.2021

Classification	Public series
Product type:	Bonded abrasives
Main industries:	General Fabrication
Further industries:	Trucks Rail Marine Bus Wind Power Windows and Doors Containers Casting and Forging Turbines Knives, cutlery Tools Shipbuilding Machinery, equipment Stamped and Shaped Parts Tubes and Profiles

<b>Product profile</b>			
Grit type:	Aluminium oxide		
Grit range (total):		FEPA F / ISO 8486	
Backing:			
Coating:			
Bonding:	Resin over resinGlass fibre		
Special coating:			
Equipment:			

Properties		Technology
Removal rate:	9 - very high	- X-LOCK
Lifetime:	9 - very long	
Finishing:		
Flexibility:	1 - very rigid	
Contact pressure:	7 - strong	

Advantages		
General Fabrication:	- Aggressive cut - High performance for stock removal - Long lifetime - Comfortable to use with little contact pressure	

## **Technical data sheet** 8933 siagrind



Applications		
General Fabrication:	<ul><li>Welded seam preparation</li><li>Removal of fillet welds</li><li>Removing solid material</li><li>Deburring</li></ul>	

Material		
General Fabrication:	Steel	• steel
	Steel	<ul><li>Unalloyed / low-alloy steel</li></ul>
	Steel	Ferrous metal

<b>Conversion forms</b>	Upper conversion	Lower conversion
	Discs	- Grinding discs

Application	Superordinate group	Subgroup
<b>E</b>	Portable machine sanding	Angle grinder
Cut:		

Details	
No suitability for:	
Sanding recommendation:	
Safety recommendation:	Observe the current valid safety recommendations at: www.sia-abrasives.com > Expertise > Safety  - Follow the general EN safety recommendations - Follow the general FEPA safety recommendations - Pay attention to the abrasives safety data sheet (available from sia Abrasives) - Use eye and face protection - Use an effective dust extraction unit or wear a fine dust mask - Use hearing protection

Communication	
Claim:	Highly efficient, hard grinding discs for iron and steel
Сору:	The hard grinding discs of the special 8933 siagrind series excel in a variety of metal applications and make for robust and efficient tools thanks to features such as high removal rates at low surface pressure and long life.

## **Technical data sheet** 8933 siagrind



Communication			
Image material:	Product Top View (PTV)	Front side: Rear side:	ID ID
	Application image	General Fabrication:	ID 4703
	Product show:		
	Macro shot:		
	Packaging image:		
	Product group image:		

Main applicationSecondary application